

FEATURES

CONTROL PANEL

- Express Control Panel for Machine Operations
- Single Plug 115V Power Supply

SEALING AREA

- Impulse Wire Seal System
- Large 16" W by 20" L Seal Area
- Standard Seal Head with Film Clamps
- Adjustable Height Sealing Platform
- Balanced Magnetic Hold Down
- Pre-Wired Seal Conveyor Ready

SHRINK TUNNEL

- Independent Tunnel Temperature Control
- Non-Stick Mesh Tunnel Belt
- Automatic Cool Down Extends Heating Element Life



OTHER FEATURES

- One Year Warranty
- Four Individually Adjustable Perforating Wheels
- Adjustable Film Cradle

MODEL SPECS

FILM CAPACITY	20" Wide (50 cm)
L BAR SEALING AREA	16" W, 20" L (41 W, 51 L cm)
INSIDE TUNNEL DIMENSIONS	20" L, 14" W, 6.5" H (51 L, 36 W, 17 H cm)
TUNNEL CONVEYOR SPEED	0-20 Feet per Minute (0-6 meters per minute)
OVERALL DIMENSIONS	76.5" L, 24" W, 32"/55" H (Table Top/Leg Kit) (195 L, 61 W, 82 H cm)
WORKING HEIGHT	36" (92 cm) - with Leg Kit
POWER REQUIREMENTS	115 Volts, Single Phase, 20 Amp
WEIGHT	380 LBS
TUNNEL WATTAGE	2,000

