

# 20HMT - HOTMELT TAPE



<b>Product Description:</b> It is an industrial strength Cold Temperature packaging tape that has been formulated to be used in applications at refrigerated temperatures or at room temperature and then stored in low temperature environments which include produce packaging, dairy facilities, meat and poultry processing plants. This product has a conformable film backing and has been combined with a consistent pressure sensitive hot melt high quality adhesive coating.	
<b>Backing:</b>	1.3 Mil BOPP Film
<b>Adhesive:</b>	Synthetic Rubber
<b>Color(s):</b>	Clear
<b>Elongation (% At Break)</b>	165% (ASTM D3759)
<b>Tensile Strength</b>	26 lbs. / in (ASTM D3759)
<b>Adhesion to Steel</b>	27-29 ozf / in (ASTM D3330)
<b>Total Thickness:</b>	1.95 Mil (ASTM D3652)
<b>Temperature Range:</b>	+35°F to +120°F (Application) -40°F to +140°F (Operating)
<b>Packaging</b>	N/A
<b>Country of Origin</b>	N/A



Certified to  
ISO 9001:2015



**Item ID**

20HMT2110C  
20HMT3110C

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. U.S. Packaging & Wrapping, LLC WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



1-800-441-5090  
4781 Highway 319 West  
Austin, Arkansas 72007