

19HMT - HOTMELT TAPE

Product Description:

Baxially-oriented polypropylene (BOPP) film carton sealing tape manufactured with pressure sensitive hot melt adhesive. Excellent processing performance with superior adhesion properties, holding force, tensile strength and reliable seals to a variety of boxes.

Backing:	1.1 Mil (Blown Film)
Adhesive:	Synthetic Rubber/Hotmelt
Color(s):	Clear
Elongation (% At Break)	165% (ASTM D3759)
Tensile Strength	26 lbs. / in (ASTM D3759)
Adhesion to Steel	47-51 ozf / in (ASTM D3330)
Total Thickness:	1.85 Mil (ASTM D3652)
Temperature Range:	+45°F to +120°F (Application) -10°F to +140°F (Operating)
Packaging	N/A
Country of Origin	N/A



Certified to
ISO 9001:2015



Item ID

19HMT2110C
19HMT3110C

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. U.S. Packaging & Wrapping, LLC WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



1-800-441-5090
4781 Highway 319 West
Austin, Arkansas 72007